Walker Bag

Finished Size: $14\frac{1}{2}$ " x 12" (excluding straps)

Fabric Requirements:

Additional Supplies:

Main Fabric: $\frac{1}{2}$ yd. Lining Fabric: $\frac{1}{2}$ yd. Batting: 2 - 16" \times 14" $\frac{3}{4}$ " wide Velcro: 5"

Pocket: $\frac{1}{4}$ yd.

Cutting Requirements:

Main Fabric - Cut 2 (front & back) - 16" x 14", Cut 3 (straps) - $9\frac{1}{2}$ " x $4\frac{1}{2}$ "

Lining Fabric - Cut 2 (front & back) - 16" \times 14"

Pocket Fabric - Cut 2 (front & back) - 16" x 6 $\frac{1}{2}$ "

Bag Construction:

Important: $\frac{1}{2}$ " Seam allowance is used throughout construction

Prepare Bag Components

- 1) Outside Front & Back
 - a. Layer the main fabric and batting, quilt as desired
 - b. Cut $1\frac{1}{2}$ " square from bottom corner of front & back.
- 2) Lining
 - a. Cut $1\frac{1}{2}$ " square from bottom corner of front & back.
- 3) Pockets
 - a. With right sides together, stitch upper and lower edges.
 - b. Turn pocket right-side out and press.
- 4) Straps
 - a. With right sides together, fold straps in half lengthwise.
 - b. Stitch together along the length and top edge.

Note: Be sure to leave the bottom edge open to turn.

- c. Turn right-side out and press.
- d. Cut 3 1 $\frac{1}{2}$ " pieces of $\frac{3}{4}$ " wide Velcro
- e. Center loopy portion on finished strap end. Stitch close to outer edge.

Assemble Components

- 1) Stitch the pocket to the walker bag front
 - a. Measure $2\frac{1}{2}$ " from bottom of the walker bag front and mark.
 - b. Place pocket bottom along this mark. Stitch close to lower edge.
 - c. Create 2 pockets by stitching down the center of the pocket (through the walker bag front).

2) Stitch Straps to Walker Bag Front

- a. Measure in 2" from left edge of the right-side of the walker bag front, using a basting stitch, stitch strap to the top edge of the walker bag front to unfinished edge of strap onto walker bag front with Velcro facing up.
- b. Measure in 2" from right edge of the right-side of the walker bag front. Repeat previous step.
- c. Center the 3rd strap. Repeat previous step.

3) Complete Outside of Walker Bag

- a. With right-sides together stitch front and back side seams. Press open.
- b. With right-sides together stitch bottom seam. Press open
- c. On INSIDE, bring side and lower seams together. Stitch across ends.

4) Complete Lining

- a. With right-sides together stich front and back seams. Press open.
- b. With right-sides together stitch bottom seam leaving an opening to turn. Press seam open.

5) Complete Walker Bag

a. With right-sides together, insert outside of walker bag into lining matching the unfinished top edges.

Note: Be sure straps are inside the bag away from the seam allowance.

- b. Stitch upper edge of walker bag.
- c. Turn walker bag right-side out. Finish stitching lining bottom seam closed. Press.
- d. Last step! Stitch the fuzzy portion of Velcro on the walker bag back. Fold the straps to the back of the walker bag to find placement. Stitch close to the outer edge.

Yea!!!
You did it!
The walker bag is complete!